



# PT23DNID

## Color Day/Night Compact Indoor/Outdoor PTZ Camera



### Features

- ⚡ 1/4" Sony™ Super HAD 480 TV Line CCD
- ⚡ 360° continuous Pan/180° Tilt with auto-flip
- ⚡ Compact (4 1/2"), lighter design
- ⚡ Color under normal illumination, B/W down to 0.01 Lux
- ⚡ IP67 Rated (Water resistant and dust proof)
- ⚡ 23X Optical, 10X Digital Zoom
- ⚡ 3 alarm inputs/1 alarm output
- ⚡ \*Can be used outside in areas where temperatures do not drop below 14°F (-10°C)

### Description

The PT23DN/ID is an indoor/outdoor Pan, Tilt, Zoom, CCTV camera, which can be mounted in- or on-ceiling (wall and roof brackets are also available). A high resolution Sony™ Super HAD CCD delivers 480TV lines of color at normal light levels, and switches to black and white mode in low light, providing an excellent minimum illumination level down to 0.01Lux using frame integration. With 23X optical zoom and 10X digital zoom, 64 presets, multi control protocols, On Screen Display (OSD) for easy setup and configuration and programmable preset tours, the PT23DN/ID provides cutting edge technology and a high degree of reliability at a very attractive price. A keyboard/joystick controller is available.

### Recommended Use:

For use indoors where a good quality Pan, Tilt, Zoom color CCTV camera is needed to produce video in low light conditions as well as normal daylight illumination.

PT23DNID SPECIFICATIONS		
Image Sensor	1/4" Sony™ Super HAD	
TV System	NTSC	
Resolution	480 TV Line	
S/N Ratio	≥ 50db	
Minimum Illumination	Color	0.5 Lux
	Black and White	0.1 Lux (B/W; ICR off)
		0.01 Lux (Amplification 64X; ICR off) 0 Lux (with IR source; ICR on)
IR Cut Filter (ICR)	Auto / Manual	
Frame Integration	2x, 4x, 6x, 8x, 12x, 16x, 32x, 64x	
Pan Range	360° Continuous	
Tilt Range	0° - 90° + auto-flip (view range: 180°)	
Between Presets	Pan: 300° Tilt: 240°	
Preset Dwell	Configurable from 1 to 255 seconds	
Presets	64	
Speed	Pan: 0.25°- 300°/Second Tilt: 0.5°- 240°/Second	
Power Source	12V DC (650mA)	
Environmental Rating	IP67; water resistant, dust proof, -10°C to 50°C	
Measurements	Diameter: 4 1/2" (114mm), Height: 7" (180mm), Weight: 3lbs (1400g)	



**INFORCE SECURITY CORP.**

DIGITAL VIDEO RECORDING AND SURVEILLANCE  
BURGLAR, SMOKE AND INTRUSION DETECTION

**Options:**



**Wall Mount**



**Pendant Mount**